









Powered by the unique IntelliCold™ Controller that provides both superior temperature uniformity and, together with improved insulation increases energy efficiency. This fridge is also packed with extra functions designed to store temperature sensitive pharmaceuticals in optimum conditions and assist busy professionals with regulatory requirements.



The simple to use four button controller is clearly labelled and allows minimum/maximum temperatures to be displayed at the touch of a button. It also shows clearly which alarm is active and why, making remedial action easy. A clear LED display shows the internal air temperature of the fridge to one decimal place.

For objective and accurate record keeping, once the warranty is



registered, a complimentary SD card will be sent which can be used to download all the temperature data and fridge functions, such a door openings, stored by the controller. This can also be used to extract short term data if, for example, there is a suspected temperature incursion; data can be downloaded and used to prove the viability of the contents. Extra reassurance is provided by controller battery back up which can record and alarm even in the event of a mains power failure.

For extra security, a digital lock can be fitted as an optional extra which solves

the problem of generic keys and for a small additional cost we can provide a manufacturers' calibration certificate from our UKAS calibration laboratory No:8898.

We are confident that this pharmacy refrigerator will provide you with many years of fault free service. However, for extra peace of mind your RLDG0210A comes complete with a FREE 5 year parts and labour warranty!*



RLDG0210A Pharmacy & Vaccine Refrigerator

Part Number	RLDG0210A
Capacity (Litres)	66
Style	Bench Top
Exterior Dimensions (HxWxD)	735 x 450 x 510mm
Interior Dimensions (HxWxD)	588 x 226 x 331mm
Energy Consumption	0.91 kWh/24h
Operating Temperature	+5°C
Interior Construction	Moulded Plastic
Exterior Construction	Powder Coated Steel
Brackets for Wall Mounting	✓
Shelves	3
Net Weight (kg)	35
Door Style	Glass
Door Hinging	Right (can be reversed at time of manufacture)
Self Closing Door	✓
Door Lock	✓
Digital Temperature Control	✓
Digital Temperature Display	✓
Internal Light	✓
High/Low Temperature Alarm	✓
Minimum/Maximum Temperature Recording	✓
Automatic Temperature & Fridge Function Data Recording	✓
Door Open Alarm	✓
Mains Failure Alarm	✓
Alarm Battery Back-Up	✓
Off Cycle Auto Defrost	✓
Fan Assisted Cooling	✓
Remote Alarm Contacts	✓
Low GWP Refrigerant	✓
Ammonia Free	✓
DH Green Book Guidelines Compliant	✓





 $^{{\}it *Terms and conditions apply, please visit the web site}\\$