



The Model T300U Trace-Level Gas Filter Correlation CO Analyzer



The Model T300U analyzer achieves low level CO measurements using the proven IR Gas Filter Correlation principle and advanced electronics. The T300U combines high sensitivity with a robust design, and wide dynamic measurement range making it ideal for ambient air quality, and other low-level applications.

— With NumaView™ premium T Series software —

- Large, vivid, and durable color touchscreen display
- All other T Series instrument platform features
- Lifetime technical support by phone and email
- Standard two-year warranty and five years on the GFC wheel

T300U Specifications

■ Ranges	Min: 0 - 100 ppb full scale Max: 0 - 100 ppm full scale (selectable, dual ranges)
■ Measurement Units	ppb, ppm, $\mu\text{g}/\text{m}^3$, mg/m^3 (selectable)
■ Zero Noise	< 10 ppb (RMS)
■ Span Noise	< 0.5% of reading (RMS) above 2.5 ppm
■ Lower Detectable Limit	< 20 ppb
■ Zero Drift	< 20 ppb/24 hours
■ Span Drift	< 0.5% of reading/24 hours above 5 ppm
■ Lag Time	10 seconds
■ Rise/Fall Time	< 60 seconds to 95%
■ Linearity	1% of full scale
■ Precision	0.5% of reading
■ Sample Flow Rate	1800 cm^3/min $\pm 20\%$
■ Power Requirements	100V-120V, 220V-240V, 50/60 Hz
■ Analog Output Ranges	10V, 5V, 1V, 0.1V (selectable)
■ Recorder Offset	$\pm 10\%$
■ Included I/O	1 x Ethernet: 10/100Base-T 2 x RS232 (300-115,200 baud) 2 x USB device ports 8 x opto-isolated digital outputs 6 x opto-isolated digital inputs 4 x analog outputs
■ Optional I/O	1 x USB com port 1 x RS485 8 x analog inputs (0-10V, 12-bit) 4 x digital alarm outputs Multidrop RS232 3 x 4-20mA current outputs
■ Operating Temperature Range	5 - 40°C 10 - 40°C (with US EPA Equivalency)
■ Dimensions (HxWxD)	7" x 17" x 23.5" (178 x 432 x 597 mm)
■ Weight	50 lbs (22.7 kg)
■ Certifications	US EPA: RFCA-1093-093

Specifications subject to change without notice.
All specifications are based on constant conditions.



TELEDYNE API
Everywhereyoulook™

9970 Carroll Canyon Road ■ San Diego, CA 92131
Ph. 858-657-9800 Fax 858-657-9816
Email api-sales@teledyne.com

For more information about the Teledyne API family of monitoring instrumentation products, call us or visit our website at:

www.teledyne-api.com

© 2019 Teledyne API
Printed documents are uncontrolled. SAL000055G
(DCN 8062) 01.10.19

